



**DEKAL
LOAD BANKS®**

DEKAL LOAD BANKS * DEKAL AGREGATI LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA * EU



DEKAL LOAD BANKS USA LLC
c/o CATALYST CONNECTION
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 * USA



Tel.: + 386 2 320 325 0 * Fax: + 386 2 320 325 2
Email: info@dekalloadbanks.com
Web: www.dekalloadbanks.com

Tel.: + 1 800 323 9172
Email: info@dekalloadbanks-us.com
Web: www.dekalloadbanks-us.com

PORTABLE RESISTIVE 28.5 V DC LOAD BANKS - DIGITAL USB

SPECIFICALLY DESIGNED RUGGED UNITS USED FOR THE TESTING AND SERVICING OF 28.5 V DC GPUS



TECHNICAL SPECIFICATION	DLB-03DU	DLB-ESS-15DU	DLB-ESS-20DU	DLB-ESS-25DU
VOLTAGE [V]	28.5 V DC ± 10 %			
LOAD REGIME OPTIONS [A]	300 A ± 20 %	300 A OR 600 A CONTINUOUS & 1500 A ± 20 % ESS PROCEDURE	300 A OR 600 A CONTINUOUS & 2000 A ± 20 % ESS PROCEDURE	300 A CONTINUOUS OR 1400 A, 2500 A ± 20 % ESS PROCEDURE
LOAD TEST PROCEDURE TYPE	/	AIRCRAFT ENGINE START SIMULATION (ESS) in duration of 35 seconds DECREASING		
LOAD TEST SPECIFICATION AT 28.5 V DC [DECREASING - ESS]	/	SEQUENCE OF 6 STEPS ENGINE START SIMULATION Step 1: 1500 A for ◊ 1 second Step 2: 1200 A for ◊ 3 seconds Step 3: 1000 A for ◊ 10 seconds Step 4: 800 A for ◊ 20 seconds Step 5: 700 A for ◊ 30 seconds Step 6: 400 A for ◊ 35 seconds	SEQUENCE OF 6 STEPS ENGINE START SIMULATION Step 1: 2000 A for ◊ 1 second Step 2: 1700 A for ◊ 3 seconds Step 3: 1200 A for ◊ 10 seconds Step 4: 1000 A for ◊ 20 seconds Step 5: 700 A for ◊ 30 seconds Step 6: 400 A for ◊ 35 seconds	SEQUENCE OF 6 STEPS ENGINE START SIMULATION Step 1: 2500 A for ◊ 1 second Step 2: 1900 A for ◊ 3 seconds Step 3: 1300 A for ◊ 10 seconds Step 4: 1000 A for ◊ 20 seconds Step 5: 700 A for ◊ 30 seconds Step 6: 400 A for ◊ 35 seconds
LOAD TEST SPECIFICATION AT 28.5 V DC [CONTINUOUS - SELECTED MANUALLY]	300 A CONTINUOUS LOAD	300 A CONTINUOUS LOAD 600 A CONTINUOUS LOAD	300 A CONTINUOUS LOAD 600 A CONTINUOUS LOAD	300 A CONTINUOUS LOAD
[DECREASING ESS - SELECTED MANUALLY]	/	1500 A DECREASING ESS	2000 A DECREASING ESS	1400 A OR 2500 A DECREASING ESS
FORCED AIR COOLING [m³/min & CFM]	22.05 m³/min - 780 CFM	44.10 m³/min - 1560 CFM	44.10 m³/min - 1560 CFM	44.10 m³/min - 1560 CFM
MEASUREMENTS & INDICATIONS				
DIGITAL POWER METER PARAMETERS USB INTERFACE SPECIFICATIONS	3 LINE HIGH BRIGHTNESS RED LED DISPLAY CLASS: ±0.5 % FS + 2C; DISPLAYED: V / A / kW USB PLUG IN CONNECTION FOR DATA PRINTOUT/ARCHIVE, INCLUDING FREE DEKAL LICENSED SOFTWARE & USB CABLE			
LIGHT INDICATION	28.5 V DC POWER INDICATION, FAILURE INDICATOR			
GPU TESTING PROCEDURE AND ENGINE DECARBONISING PROPOSAL(*)	LOAD 300A for ◊ 30 minutes	*LOAD 300 A or 600 A ◊ 30 / 15 minutes ESS in 6 STEPS 100% → 0% ◊ 35 seconds	*LOAD 300 A ◊ 30 minutes or ESS in 6 STEPS 100% → 0% ◊ 35 seconds	
OPERATING TEMPERATURE [°C / °F]	from -20 °C to 55 °C / from -4 °F to 122 °F			
NOISE LEVEL [dB] AT DISTANCE [m/Ft]	< 70 dB(A) at the distance of 7m / 23Ft			
DIMENSIONS & WEIGHT				
LOAD BANK SIZE [L x W x H] mm / Kg LOAD BANK SIZE [L x W x H] In / Lbs	570 x 230 x 450 / 18 22.5 x 9 x 18 / 39	570 x 230 x 450 / 20 22.5 x 9 x 18 / 44	570 x 230 x 450 / 25 22.5 x 9 x 18 / 55	570 x 230 x 450 / 26 22.5 x 9 x 18 / 57
TRANSPORT CASING [L x W x H] mm / Kg TRANSPORT CASING [L x W x H] In / Lbs	620 x 280 x 690 / 17 24.4 x 11 x 27.2 / 37	620 x 280 x 690 / 17 24.4 x 11 x 27.2 / 37	620 x 280 x 690 / 17 24.4 x 11 x 27.2 / 37	620 x 280 x 690 / 17 24.4 x 11 x 27.2 / 37
LOAD BANK PAINTING / TRANSPORT CASING	POWDER COATING FINE STRUCTURE 71319 IGP, SWISS QUALITY / HIGH GRADE ALUMINUM			

Including transport carrying case per unit / All specifications are subject to change without further notice