



**DEKAL
LOAD BANKS®**

DEKAL LOAD BANKS * DEKAL AGREGATI LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA * EU



DEKAL LOAD BANKS USA LLC
c/o CATALYST CONNECTION
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 * USA



Tel.: + 386 2 320 325 0 * Fax: + 386 2 320 325 2
Email: info@dekalloadbanks.com
Web: www.dekalloadbanks.com

Tel.: + 1 800 323 9172
Email: info@dekalloadbanks-us.com
Web: www.dekalloadbanks-us.com

ADVANTAGES OF DEKAL LOAD BANKS

- ▶ **Simple operation** suitable for non-trained operators
- ▶ **Silent operations** < 70 dB(A) at the distance of 7m / 23Ft
- ▶ Suitable for **workshop and/or airside operation**
- ▶ **Environmental operating temperature** from -20 °C to 55 °C / -4 °F to 122 °F
- ▶ **Transport casing** with pull up handle as standard for each load bank
- ▶ **Free DEKAL licensed software application & proper drivers included**
- ▶ **All measurements possible to archive & printout, including diagram graphics**
- ▶ **Effective way of monitoring and displaying measurement data**
- ▶ **High instrument indication accuracy**
- ▶ Triple thermal protection - **extremely resistant** to high temperature
- ▶ **Cant protection** - load bank works only in horizontal position
- ▶ Aluminum housing and **non-corrosive parts**
- ▶ **High component quality control** by manufacturer
- ▶ **High reliability** - effective standardization process
- ▶ Isolated jack sockets - **unique user friendly safety feature** for external voltage test
- ▶ Spare parts availability and **accurate on-time deliveries**
- ▶ **Short worldwide delivery period** with tracking feature & insurance
- ▶ **2 years full warranty with extension option** for all DEKAL load banks
- ▶ CE certification - health, safety, and environmental protection standards
- ▶ Made for GPU's testing procedure according to ISO 6858, DFS 400, ARP 5015
- ▶ Classification CE marking, DIN, VDE, IEC, IP 21 protection rate level



NCAGE CODE: 1267Q



Excellent SME



Creditworthiness Rating



D-U-N-S®
REGISTERED™